



AUC48R Refrigerator

AUC48F

Two Door Under-Counter/ Worktop Refrigerators and Freezers

- Tested to NSF Standard 7 requirements for open food storage.
- All Arctic Air products come with full one year parts and labor warranties and a five year compressor warranty.



Arctic Air products must pass numerous quality control inspections throughout the manufacturing process.

All products are operated and monitored for a minimum of thirteen hours prior to packaging and shipping.

Two Door Under-Counter Worktop Refrigerators and Freezers

Stainless design. Stellar performance. Superior value.

- Solid door construction with foamed-in-place recessed handle.
- Freezer doors have integral factory installed heating element to eliminate condensation.
- Magnetic door gaskets are removable and replaceable without tools.
- Exterior cabinet construction consists of full stainless steel front and sides.
- Interior cabinet is bright white ABS liner with full stainless steel floor with coved corners.
- Larger fan motors and blades for more efficient air flow ensuring faster recovery times.



- Condensate heating element built into condensate pan for efficient evaporation of excess water.
- Electronic thermostat with external digital LED display for accurate control and easy reading.
- Two adjustable, heavy-duty epoxy coated wire shelves.
- Self contained capillary tube system using environmentally friendly CFC free refrigerant (R404A in freezers and R134A in refrigerators).

- All units come standard with heavy-duty worktop surface.
- Standard top panel is removable for use in lower height applications (reduces total height by 1.5").
- Self closing doors that remain open at 90 degrees.
- Easy to mount casters (two lockable) are standard with all units.
- Tested to NSF Standard 7 requirements for open food storage.
- All Arctic Air products come with full one year parts and labor warranties and a five year compressor warranty.


Model Number	Exter Width	nal Dimer Depth*		Doors	Shelves	Cubic Feet	Temperature Range	Cord Length	HP	Amps	NEMA Plug	Crated Weight (lbs.)
AUC48R	48.25"	30.0"	35.625"	2	2	12	33°F to 41°F	8	3/8	5	5-15P	260
AUC48F	48.25"	30.0"	35.625"	2	2	12	-10°F to +10°F	8	5/8	9	5-15P	280

^{*}Depth with door open 90° — AUC48R/AUC48F = 54.75"

Optional Backsplash Accessory (#65160)

Backsplash is easily mounted and comes with NSF food grade silicone sealant for seam.

Width= 48.25" Depth= 1" Height=4"



Each kit contains one shelf and four mounting clips.









^{**}Height includes 3" for casters. Height with worktop panel removed = 34.125"