



# ELEVATION SERIES GRANDE CUBE MAKER

## CIMO836/O835

**Ice-O-Matic**  
Ice. Pure and Simple

### Model:

☐ CIMO836

☐ CIMO835



CIMO836 ON B55

## Features and Benefits

- 30.25" (768 mm) wide space-saving design.
- Produces up to 845 lbs (383 kg) of ice per day.
- **Energy and Environment**
  - Exceeds new 2018 DOE (Department of Energy) regulations.
  - Up to 20% more energy efficient than other models.
  - Environmentally friendly, including BPA-free plastic and recyclable parts.
- **Sanitation**
  - Plastic Food Zone eliminates hard-to-clean nooks and crannies, allowing for effortless wipe down and easy, long-lasting sanitation.
  - Built in Agion® ensures unbeatable antimicrobial protection.
  - Smart LED light indicates machine status and when cleaning is required.
  - Simple, one-touch controls for sanitization and descaling.
  - BPA-free snap-in, snap-out dishwasher-safe components.
- **Unique Dual Exhaust** - Air-cooled machines are designed to discharge hot air from both the side and top of the unit, increasing installation flexibility and reducing the potential of obstructed exhaust.
- **Universal Smart Harness™** control board simplifies installation and servicing with better access, digital diagnostics, universal components and common configuration.

## Bin Chart Kits for Combining Wider Bins with Smaller Models

### Ice Form



### GRANDE CUBE

#### GRANDE CUBE DIMENSIONS

W x D x H (in.)	1 1/4 x 1 1/8 x 7/8
W x D x H (mm)	31 x 29 x 22

ICE STORAGE BINS											
Model No.	B25	B40	B42	B55	B700	B110	B1000	B1300	B1325	B1660	
Capacity	242 lbs (110 kg)	344 lbs (156 kg)	351 lbs (160 kg)	510 lbs (232 kg)	680 lbs (308 kg)	854 lbs (388 kg)	1000 lbs (454 kg)	1,320 lbs (599 kg)	1,325 lbs (601 kg)	1,660 lbs (753 kg)	
Width	30 in (762 mm)	30 in (762 mm)	22 in (559 mm)	30 in (762 mm)	30 in (762 mm)	48 in (1,219 mm)	48 in (1,219 mm)	48 in (1,219 mm)	60 in (1,524 mm)	60 in (1,524 mm)	
Kits	Kit Not Required		N/A	Kit Not Required		BPF-1	Hold Down Securement Recommended				
CIMO836											
CIMO835											

\*See Ice-O-Matic Price List for Adapter Kits to combine ice makers with most available ice/beverage dispensers.

## Options & Accessories

WATER FILTERS		
Ice Machine Model	Manifold	
	System	Replacement
CIMO836	IFQ1	IOMQ (1)
CIMO835		

Note: All modular cube CIM units can be installed with the O<sub>3</sub>-Matic™ Ozone Delivery System.

## Ice Maker Warranty

COMMERCIAL WARRANTY	
Ice Maker	3 YEARS parts and labor
Evaporator and Compressor	5 YEARS parts
Evaporator (when enrolled in our filter program)	7 YEARS parts and labor



CIMO836/O835 GRANDE CUBE MAKER



# ELEVATION SERIES GRANDE CUBE MAKER

## CIMO836/O835

**Ice-O-Matic®**  
Ice. Pure and Simple®



CIMO836/O835 GRANDE CUBE MAKER

### Air Cooled

Please note: air-cooled units require 6" (152 mm) clearance for air intake and exhaust.

- A. Ice maker potable water in,  $\frac{3}{8}$ " FPT.
- B. Ice maker water out,  $\frac{3}{4}$ " FPT.
- C. Hole for electrical connections,  $\frac{7}{8}$ ".
- D. Electrical connection junction box,  $\frac{7}{8}$ ".

Dual Exhaust for Installation Flexibility



## Operating Requirements

MINIMUM		MAXIMUM	
		60 Hz	50Hz
Ambient Temp. Range Air	50 °F (10 °C)	100 °F (38 °C)	110 °F (43 °C)
Water Temp.	40 °F (4.4 °C)		
Water Pressure	20 PSIG (1.4 BAR)	80 PSIG (5.5 BAR)	

## Dimensions

ALL MODELS	
W x D x H (in.)	30.25 x 24.25 x 26.9
W x D x H (mm)	768 x 616 x 683

## Specifications

Model Number	Cond. Unit	Half-Cube Ice Production per 24hrs		Water Usage gallons per 100 lbs of Ice 90°F air/70°F water		kWH Used per 100 lbs of ice @ 90°F air/ 70°F water	Voltage Characteristics	Min. Circuit Ampacity	Fuse Size	Approx. BTUs per hour
		70°F air/ 50°F water lbs (kg)	90°F air/ 70°F water lbs (kg)	Potable	Condenser					
CIMO836	Air	800 (363)	645 (293)	19.0	N/A	5.4	208-230/60/1	12.3	20	18,200
CIMO835	Air	845 (383)	710 (322)	18.0		5.7	220-240/50/1	13.5		19,300

\* Daily ice production based on grande cube configuration.

Notes:  
Number of Wires: 3 (including ground)  
Approx. Shipping Weight lbs (kg): CIMO836A 230 (105) • CIMO835A 230 (105)  
Refrigerant Type: R404A