STORMWATER CONTROL STRUCTURE PREFORMED SCOUR HOLE MAINTENANCE AGREEMENT

Respons	Project:ible Party
•	Phone #:
	Address:
I. Monthly	, or after ever runoff producing rainfall, whichever comes first:
a.	Remove all accumulated litter, debris, and sediment from the preformed scour hole.
b.	Inspect preformed scour hole for evidence of scour, undercutting, settlement of the structure, and concentrated flows downhill of the structure.
C.	A level elevation shall be maintained across the entire flow-spreading structure at all times. Repair or replace the preformed scour hole if it is damaged.
d.	Reseed any denuded areas with permanent grass seed of the Owner's choice. Remove woody vegetation from the preformed scour hole and surrounding area. Eroded rills and gullies should be filled with topsoil, compacted and then reseeded.
II. Quarte	rly:
a.	Thoroughly inspect the stormwater drainage system and preformed scour hole for proper functioning.
b.	Perform all required maintenance for the Monthly Inspection.
III. Gener	al:
a.	All components of the preformed scour hole are to be kept in good working order.
b.	In case the ownership of the abovementioned property transfers, the current owner shall, within thirty (30) days of transfer of ownership, notify the Wake County Environmental Services, Watershed Section of such ownership transfer.
	hereby acknowledge that I am the financially responsible naintenance of this structure. I will perform the maintenance as outlined above, as part tificate of Compliance with Stormwater Regulations received for this project.
Signature	Date:
before me	, a Notary Public for the State of, County of, do hereby certify that personally appeared this day of, 202_ and acknowledge due execution of the instrument. Witness my hand and official seal,
Seal	My commission expires: